

SUNSTREAM

SUNLIFT SLX





**FIRST BOAT
IN THE WATER
WINS.**

SUNSTREAM HELPS YOU ENJOY YOUR BOAT MORE.

Boating is our passion and, like you, we envisioned a future that minimized the hassles and frustrations of getting your boat in and out of water, accessing the hull and covering the boat. For over 25 years, we've been leading the industry by elevating boating experiences all over the globe. Our award winning engineering and design continue to push the boundaries of what's possible by producing many of the world's first freestanding hydraulic boat lifts and automatic cover systems. You're invited to the future of boating.

Boat more, boat easier, boat better.



FREE-STANDING
HYDRAULIC LIFT



FREE-FLOATING
HYDRAULIC LIFT



AUTOMATIC BOAT
COVER SYSTEM



SUNLIFT SLX

SUNLIFT SLX

The Best Just Got Better.

The Sunlift SLX is the new standard in free-standing hydraulic boat lifts. Sunstream has a rich heritage of innovation and it continues to drive us today more than ever. We're boaters too and we believed boating could be more fun and less hassle. The Sunlift SLX is the culmination of meticulous engineering, unparalleled manufacturing and technological advancement.

Well designed to lift boats and drop jaws.





- 1 Adjustable Width Bunks
- 2 Adjustable Range Option
- 3 Side Shift
- 4 Stainless Steel Cylinders & Hoses

- 5 Hydraulic Boot & Scrubber
- 6 Cylinders Aligned with Frame
- 7 Soft Stop
- 8 Bronze Bushings

- 9 Stylish Domed Head Pins
- 10 Set Bolt in Leg Sleeves
- 11 Oval Cast Feet
- 12 SuperBunks™

- 13 3.25in Wide Beams
- 14 Thick Wall Aluminum Construction
- 15 Bronze Nuts
- 16 GravityLock™



FLAWLESS HULL FIT

The SunLift SLX is the only hydraulic lift that has adjustable width bunks to achieve an ideal boat fit. Additionally, the boat height over water can be set with an adjustable lifting range up to 6.5 feet. The frame can also shift laterally to minimize the distance of the boat to dock to allow safe boarding every time. Sunstream SuperBunks™ softly cradle the hull and will last for years without wear. The Superbunks™ act as spring beams, which spread the load over the entire bunk, creating a comfortable resting spot for your boat without pressure points.

SUPERIOR HYDRAULICS

The hydraulic system is the heart of a hydraulic lift and is key for reliability and performance. The SunLift SLX never compromises on durability with all stainless steel cylinders, a patented shaft boot with scrubber and scraper seal, double braid stainless hoses, and stainless fittings. The SLX has elite performance with a premium pressure balanced pump (vs a basic fixed gear pump) that has up to 20% more efficiency, higher speed, quieter sound, and does not lose lifting capacity over time. The SoftStop™ eases the hydraulic power for a smooth finish to the top position.

MODERN FRAME

The SunLift SLX modern frame has a beauty that is worthy of displaying your boat. The frame has superior stiffness with the cylinders aligned with frame, fewer bolts, and a set bolt to remove movement in the leg socket. The Sunstream SLX boasts the best range of specifications on the market, with the highest lifting range, shallowest water depth, fastest speed, and capacities to 30,000lbs. Optional Leg Jacks can give an additional 3ft of range to lakes with seasonal fluctuation. The over-center GravityLock™ gives you maximum peace of mind.



Optional bow stop shown

BLUETOOTH & APP



Sunstream's optional Bluetooth transmitter and smartphone app give you the power to lift your boat with your phone! It also gives important lift diagnostics to prevent a problem from becoming a problem. Bluetooth technology has more consistent range, and is more responsive. Built-in security features protect your boat, and 'depressurize' is ideal for seasonal users.



SWIFTSHIELD

Sunstream's SwiftShield automatic boat cover system helps you to use your boat more and protects your investment. Say farewell to the frustration that comes with traditional boat covers and hello to boating anytime you want. Be on the water in just 30 seconds with the push of a remote.

SPECIAL CONFIGURATIONS



Shallow Water
SW



Pontoon/Tritoon
Lifting with Toons
PON



Pontoon/Tritoon
Underdeck Lifting
UDK



3' Range
B3

MEDIUM Family B

LARGE Family B

X-LARGE Family C

| | SLX5010B4 | SLX6512B4 | SLX8012B4 | SLX9012B5 | SLX10014B5 | SLX12016B5 | SLX16018C5 | SLX20020C5 | SLX24022C5 | SLX30022C5 |
|--|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|
| Capacity at Standard Range | 5,000lb 2268kg | 6500lb 2948kg | 8000lb 3629kg | 9000lb 4082kg | 10000lb 4536kg | 12000lb 5443kg | 16000lb 7257kg | 20000lb 9072kg | 24000lb 10886kg | 30000lb 13608kg |
| Standard Range | 4ft 1.2m | 4ft 1.2m | 4ft 1.2Mm | 5ft 1.52m |
| Bunk Length | 10ft 3m | 12ft 3.7m | 12ft 3.7m | 12ft 3.7m | 14ft 4.2m | 16ft 4.9m | 18ft 5.5m | 20ft 6m | 22ft 6.7m | 22ft 6.7m |
| Frame Width* | 102.5in 260.3cm | 102.5in 260.3cm | 132.5in 336.5cm | 132.5in 336.5cm | 132.5in 336.5cm | 132.5in 336.5cm | 152.5in 387.3cm | 152.5in 387.3cm | 152.5in 387.3cm | 152.5in 387.3cm |
| Frame Length** | 120.5in 306cm | 144.4in 366.7cm | 144.8in 367.7cm | 145.9in 370.5cm | 169.4in 430.2cm | 193.4in 491.2cm | 173.6in 440.9cm | 197.6in 501.9cm | 221.6in 562.8cm | 221.6in 562.8cm |
| Cylinders | 2 | 2 | 2 | 4 | 4 | 4 | 4 | 4 | 4 | 6 |
| Min Depth Under Keel/Skeg (typ) | 7in 18cm | 7in 18cm | 8in 23cm | 8in 23cm | 8in 23cm | 8in 23cm | 10in 25cm | 10in 25cm | 10in 25cm | 10in 25cm |
| Shallow Water Min Depth Under Keel/Skeg (typ) | 0-3in 0-8cm | 0-3in 0-8cm | 0-3in 0-8cm | 0-3in 0-8cm | 0-3in 0-8cm | 0-3in 0-8cm | N/A | N/A | N/A | N/A |

*Frame width measured outside edges of leg sleeves

**Frame length measured front of forward crossbeam to back of rear crossbeam

| Capacity at: | SLX5010B4 | SLX6512B4 | SLX8012B4 | SLX9012B5 | SLX10014B5 | SLX12016B5 | SLX16018C5 | SLX20020C5 | SLX24022C5 | SLX30022C5 |
|----------------------|------------------|------------------|------------------|------------------|-------------------|-------------------|-------------------|-------------------|--------------------|--------------------|
| 3ft .91m | 5000lb 2268kg | 6500lb 2948kg | 8000lb 3629kg | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| 4ft 1.2m | 5000lb 2268kg | 6500lb 2948kg | 8000lb 3629kg | 9000lb 4082kg | 10000lb 4536kg | 12000lb 5443kg | 16000lb 7257kg | 20000lb 9072kg | 24000lb 10886kg | 30000lb 13608kg |
| 5ft 1.52m | 5000lb 2268kg | 6000lb 2721kg | 7400lb 3357kg | 9000lb 4082kg | 10000lb 4536kg | 12000lb 5443kg | 16000lb 7257kg | 20000lb 9072kg | 24000lb 10886kg | 30000lb 13608kg |
| 6ft 1.82m | 4500lb 2041kg | 5000lb 2268kg | 6000lb 2722kg | 8500lb 3856kg | 9000lb 4082kg | 10000lb 4536kg | 16000lb 7257kg | 19000lb 9072kg | 20000lb 9072kg | 26000lb 11793kg |
| 6.5ft 2m | 4000lb 1814kg | 4500lb 2041kg | 5500lb 2495kg | 7500lb 3402kg | 8000lb 3629kg | 9000lb 4082kg | 16000lb 7257kg | 17000lb 7711kg | 18000lb 8165kg | 24000lb 10886kg |

With B3 Config

Cut Range

Standard Range

With AR18 Accy.

With AR30 Accy.

SUNSTREAM

SUNLIFT SLX




FLOATLIFT
Free-floating
Hydraulic Boat Lift



SWIFTSHIELD
Automatic Cover
System



SUNLIFT LEGACY
Original Hydraulic
Free-standing Lift



SUNPORT2
PWC Drive-On
Dock

BOAT MORE,
BOAT EASIER,
BOAT BETTER.

sunstreamboatlifts.com